

RSFC_parcellation_AZSnyder_OHBM2017

Different parcellation techniques give different answers

- Sulci & gyri (AAL) (Tzourio-Mazoyer et al., 2002)
- Histology (Brodmann areas)
- Gene expression (<https://www.alleninstitute.org>)
- Receptor density mapping (Amunts and Zilles, 2015; Zilles and Amunts, 2009)
- RSFC (Biswal et al., 1995)

What is RSFC?

- ICA vs. seed-based correlation (Beckmann et al., 2005; Fox et al., 2005; Shehzad et al., 2009)
- RSFC data quality issues
 - Artifact (Behzadi et al., 2007; Jo et al., 2010; Power et al., 2012; Power et al., 2014)
 - Quantity of RSFC data (Laumann et al., 2015)
 - State-dependence (Tagliazucchi and Laufs, 2014)
- RSFC is hierarchically organized (Cordes and Nandy, 2006; Doucet et al., 2011; Hacker et al., 2013; Lee et al., 2012)

RSFC as a parcellation tool

- Inner product-based RSN clustering (Lee et al., 2012; Yeo et al., 2011)
- Graph-theoretic parcellation (Power et al., 2011)
- Boundary mapping and parcel homogeneity evaluation (Cohen et al., 2008; Wig et al., 2014a; Wig et al., 2014b)
- RSFC parcellation consistency across studies (Gordon et al., 2016)
- Relation of RSNs to function (Smith et al., 2009; Yeo et al., 2015)
- Gradients vs. seed-mapping can yield different answers (Buckner and Yeo, 2014)
- V1-V2 Parcellation and genetics vs. experience in development (Striem-Amit et al., 2015)

Individual RSFC differences (Dubois and Adolphs, 2016)

- Individual differences in RSFC (Laumann et al., 2015; Mueller et al., 2013)
- Supervised vs. unsupervised classification (Hacker et al., 2013)

Amunts, K., Zilles, K., 2015. Architectonic Mapping of the Human Brain beyond Brodmann. *Neuron* 88, 1086-1107.

Beckmann, C.F., DeLuca, M., Devlin, J.T., Smith, S.M., 2005. Investigations into resting-state connectivity using independent component analysis. *Philosophical transactions of the Royal Society of London. Series B, Biological sciences* 360, 1001-1013.

Behzadi, Y., Restom, K., Liau, J., Liu, T.T., 2007. A component based noise correction method (CompCor) for BOLD and perfusion based fMRI. *NeuroImage* 37, 90-101.

Biswal, B., Yetkin, F.Z., Haughton, V.M., Hyde, J.S., 1995. Functional connectivity in the motor cortex of resting human brain using echo-planar MRI. *Magn Reson Med* 34, 537-541.

Buckner, R.L., Yeo, B.T., 2014. Borders, map clusters, and supra-areal organization in visual cortex. *NeuroImage* 93 Pt 2, 292-297.

- Cohen, A.L., Fair, D.A., Dosenbach, N.U., Miezin, F.M., Dierker, D., Van Essen, D.C., Schlaggar, B.L., Petersen, S.E., 2008. Defining functional areas in individual human brains using resting functional connectivity MRI. *NeuroImage* 41, 45-57.
- Cordes, D., Nandy, R.R., 2006. Estimation of the intrinsic dimensionality of fMRI data. *NeuroImage* 29, 145-154.
- Doucet, G., Naveau, M., Petit, L., Delcroix, N., Zago, L., Crivello, F., Jobard, G., Tzourio-Mazoyer, N., Mazoyer, B., Mellet, E., Joliot, M., 2011. Brain activity at rest: a multiscale hierarchical functional organization. *Journal of neurophysiology* 105, 2753-2763.
- Dubois, J., Adolphs, R., 2016. Building a Science of Individual Differences from fMRI. *Trends in cognitive sciences* 20, 425-443.
- Fox, M.D., Snyder, A.Z., Vincent, J.L., Corbetta, M., Van Essen, D.C., Raichle, M.E., 2005. The human brain is intrinsically organized into dynamic, anticorrelated functional networks. *Proceedings of the National Academy of Sciences of the United States of America* 102, 9673-9678.
- Gordon, E.M., Laumann, T.O., Adeyemo, B., Huckins, J.F., Kelley, W.M., Petersen, S.E., 2016. Generation and Evaluation of a Cortical Area Parcellation from Resting-State Correlations. *Cerebral cortex* 26, 288-303.
- Hacker, C.D., Laumann, T.O., Szrama, N.P., Baldassarre, A., Snyder, A.Z., Leuthardt, E.C., Corbetta, M., 2013. Resting state network estimation in individual subjects. *NeuroImage* 82, 616-633.
- Jo, H.J., Saad, Z.S., Simmons, W.K., Milbury, L.A., Cox, R.W., 2010. Mapping sources of correlation in resting state FMRI, with artifact detection and removal. *NeuroImage* 52, 571-582.
- Laumann, T.O., Gordon, E.M., Adeyemo, B., Snyder, A.Z., Joo, S.J., Chen, M.Y., Gilmore, A.W., McDermott, K.B., Nelson, S.M., Dosenbach, N.U., Schlaggar, B.L., Mumford, J.A., Poldrack, R.A., Petersen, S.E., 2015. Functional System and Areal Organization of a Highly Sampled Individual Human Brain. *Neuron* 87, 657-670.
- Lee, M.H., Hacker, C.D., Snyder, A.Z., Corbetta, M., Zhang, D., Leuthardt, E.C., Shimony, J.S., 2012. Clustering of resting state networks. *PLoS One* 7, e40370.
- Mueller, S., Wang, D., Fox, M.D., Yeo, B.T., Sepulcre, J., Sabuncu, M.R., Shafee, R., Lu, J., Liu, H., 2013. Individual variability in functional connectivity architecture of the human brain. *Neuron* 77, 586-595.
- Power, J.D., Barnes, K.A., Snyder, A.Z., Schlaggar, B.L., Petersen, S.E., 2012. Spurious but systematic correlations in functional connectivity MRI networks arise from subject motion. *NeuroImage* 59, 2142-2154.
- Power, J.D., Cohen, A.L., Nelson, S.M., Wig, G.S., Barnes, K.A., Church, J.A., Vogel, A.C., Laumann, T.O., Miezin, F.M., Schlaggar, B.L., Petersen, S.E., 2011. Functional network organization of the human brain. *Neuron* 72, 665-678.
- Power, J.D., Mitra, A., Laumann, T.O., Snyder, A.Z., Schlaggar, B.L., Petersen, S.E., 2014. Methods to detect, characterize, and remove motion artifact in resting state fMRI. *NeuroImage* 84, 320-341.
- Shehzad, Z., Kelly, A.M., Reiss, P.T., Gee, D.G., Gotimer, K., Uddin, L.Q., Lee, S.H., Margulies, D.S., Roy, A.K., Biswal, B.B., Petkova, E., Castellanos, F.X., Milham, M.P., 2009. The resting brain: unconstrained yet reliable. *Cerebral cortex* 19, 2209-2229.
- Smith, S.M., Fox, P.T., Miller, K.L., Glahn, D.C., Fox, P.M., Mackay, C.E., Filippini, N., Watkins, K.E., Toro, R., Laird, A.R., Beckmann, C.F., 2009. Correspondence of the brain's functional architecture during activation and rest. *Proceedings of the National Academy of Sciences of the United States of America* 106, 13040-13045.
- Striem-Amit, E., Ovadia-Caro, S., Caramazza, A., Margulies, D.S., Villringer, A., Amedi, A., 2015. Functional connectivity of visual cortex in the blind follows retinotopic organization principles. *Brain : a journal of neurology* 138, 1679-1695.
- Tagliazucchi, E., Laufs, H., 2014. Decoding wakefulness levels from typical fMRI resting-state data reveals reliable drifts between wakefulness and sleep. *Neuron* 82, 695-708.
- Tzourio-Mazoyer, N., Landeau, B., Papathanassiou, D., Crivello, F., Etard, O., Delcroix, N., Mazoyer, B., Joliot, M., 2002. Automated anatomical labeling of activations in SPM using a macroscopic anatomical parcellation of the MNI MRI single-subject brain. *NeuroImage* 15, 273-289.

- Wig, G.S., Laumann, T.O., Cohen, A.L., Power, J.D., Nelson, S.M., Glasser, M.F., Miezin, F.M., Snyder, A.Z., Schlaggar, B.L., Petersen, S.E., 2014a. Parcellating an individual subject's cortical and subcortical brain structures using snowball sampling of resting-state correlations. *Cerebral cortex* 24, 2036-2054.
- Wig, G.S., Laumann, T.O., Petersen, S.E., 2014b. An approach for parcellating human cortical areas using resting-state correlations. *NeuroImage* 93 Pt 2, 276-291.
- Yeo, B.T., Krienen, F.M., Eickhoff, S.B., Yaakub, S.N., Fox, P.T., Buckner, R.L., Asplund, C.L., Chee, M.W., 2015. Functional Specialization and Flexibility in Human Association Cortex. *Cerebral cortex* 25, 3654-3672.
- Yeo, B.T., Krienen, F.M., Sepulcre, J., Sabuncu, M.R., Lashkari, D., Hollinshead, M., Roffman, J.L., Smoller, J.W., Zollei, L., Polimeni, J.R., Fischl, B., Liu, H., Buckner, R.L., 2011. The organization of the human cerebral cortex estimated by intrinsic functional connectivity. *Journal of neurophysiology* 106, 1125-1165.
- Zilles, K., Amunts, K., 2009. Receptor mapping: architecture of the human cerebral cortex. *Current opinion in neurology* 22, 331-339.

Tools to parcellate the brain and its relation to function: Part II

Resting state functional connectivity

A. Z. Snyder

Washington University School of Medicine

June 25, 2017


Course Objectives


- The fundamental techniques used to analyze resting state BOLD fMRI data
- How a parcellation scheme can be built using these techniques
- Special challenges that result from the hierarchical organization of resting state networks
- How to use supervised learning to build on the data-driven techniques and address these challenges

There are many ways to parcellate the cerebral cortex.


Gyral/sulcal anatomy (AAL)

4







Brodmann's cytoarchitectonic map (1909):
Lateral surface



Brodmann's cytoarchitectonic map (1909):
Medial surface

Receptor density (Zilles & Amunts 2009)




Introduction to resting state functional connectivity (RSFC)


Seed-based Correlation Mapping

- Definition: Spatial map of brain regions correlated with mean time-course of region of interest

Task Response





Regions Correlated with “b”




- Motivation: Regions that correspond to similar brain functions have spontaneously correlated signals

Seed-based Correlation Mapping









sICA vs. seed-based mapping TECHNICAL COMPARISON 12

	Spatial ICA (sICA)	Seed-based correlation mapping
Major attribute	Data-driven (“blind”)	Directed at pre-determined regions and functional systems
Algorithmic basis	Maximization of component independence	Computation of ROI-voxel correlation (over time)
Noise reduction strategy	Elimination of noise components after sICA	Regression prior to correlation mapping
Combing results over multiple subjects	Concatenation of datasets (“tensor ICA”)	Average maps over subjects

Clustering Approaches


- Fuzzy C-means:
 - Each voxel yields one correlation map
 - Clusters are formed from groups of maps with high spatial similarity




- Multiple “good” answers

Clustering Approaches


7 Clusters



17 Clusters



Sub-regions are nested




Multiple local minima in cluster instability

Reproducible, hierarchical organization


Graph Theoretic Approaches

15



RSNs are Hierarchically Organized

- Agglomerative ICA results:
 - RSNs(23) $\in$ Modules (5) $\in$ Systems(2)



Yeo et al.
(2011)
Clustered
FC Maps






Lee et al.
(2012)
Clustered
FC Maps

Smith et al.
(2013)
ICA






Doucet et al.
(2011)
Agglomerative
ICA

Power et al.
(2011)
Graph
Modularity






Dorsal Attention








Ventral Attention







Sensorimotor






Visual








**Fronto-parietal
Control System**



Language



Default Mode




Parcellation using RSFC gradient mapping




Unlike political maps, resting state network (RSN) maps are not disjoint. Consequently, RSN-based parcellations necessarily involve weighting and thresholding.


A Temporal Correlation



B Spatial Correlation



C Spatial Principal Component Analysis



Hacker et al.,
NeuroImage 2013;
82:616-33


G.S. Wig et al. / NeuroImage 93 (2014) 276–291


289


2) Deform and resample data to 32k vertex fs_LR atlas surface

3) Generate average full volume RSFC maps for each vertex



4) Spatial correlation between each pair of vertices RSFC map










RSFC gradients are very unequal in magnitude. The significance of this essentially topological finding remains unknown.






0 5
Spatial Gradient





0 1
Correlation (r)

RSFC parcellations in relation to task-fMRI responses



RS-fMRI
sICA
↓
Task-fMRI
↓











(a) Intrinsic organization of functionally specialized regions



Obtaining good RSFC results requires careful attention to artifact reduction and long acquisitions.



Wise et al., NeuroImage 2004;21-1652-64



Gray Matter General Linear Model

Overall Signal Stimulus Response Linear+Constant Terms Physiological Noise Random Noise

$$b_{gray} = Xh + Sd + Pc + n$$

$$P_{est} = \begin{bmatrix} - & - & - \\ - & PC_1 & - \\ - & - & - \\ - & PC_2 & - \\ - & - & - \\ - & \vdots & - \\ - & PC_N & - \\ - & - & - \end{bmatrix}$$

Select first N principal components

Temporal Principal Component Analysis

$$b_{nROI} = Pc + n$$

Detrend

$$b_{nROI} = Sd + Pc + n$$

Noise ROI General Linear Model


- 1) Anatomical noise ROI - White matter and CSF-only voxels
- 2) tSTD noise ROI - Top 2% of voxels per slice with highest temporal standard deviation

Behzadi et al.,
NeuroImage 2007;
37:90-101


← CompCor scheme

A


Subset 1




B





Subset 2



C



Individual RSN differences




Introduction to supervised classification

Supervised vs. Unsupervised Approaches

Example application:
Automated postal mail sorting

Unsupervised Learning:

(e.g., cluster analysis, ICA)




Bresson et al., 2012

Discovery:

These are the characters of the decimal system

Supervised Learning

- discriminant analysis (LDA/QDA)
- neural networks
- support vector machines



Classification:


This image represents the number "2"

Setting up the problem

Input Space (X):
Array of pixels

Output Space (Y):

Class	Desired Value
"1"	0
"2"	1
"3"	0
"4"	0
...	0





$$Y \approx f(X, \theta)$$

Θ - learned model parameters

Setting up the problem

Input Space (X):
Array of voxels



Output Space (Y):

Class	Desired Value
"DAN"	0
"VAN"	0
"SMN"	1
"VIS"	0
...	0

$$Y \approx f(X, \theta)$$


- Training Data:
 - Set of seed-based correlation maps
 - Must include variability across regions and subjects
 - Each seed assigned to one RSN

Supervised Learning

- Theory:
 - Learn an underlying function that maps correlation map topography to RSN identity
- Application:
 - Create correlation map for every region in the brain
 - Apply learned function to these maps
 - Result: map of RSN identity throughout the brain

RSN Classification Technique

- Compute a correlation map for each point in the brain
- Estimate membership in each RSN class based on learned function



Generalizability to Untrained Brain Regions

- Correct extrapolation to regions not in the training data (cerebellum, thalamus in this example) indicates learning of an underlying function.

